

AGIP EXIDIA EP



AGIP EXIDIA EP oils are suitable for lubricating machine tool guides. The oils are paraffin-based with special greasing, anti-rust and anti-sticking additives (EP). The various grades of oil fall under the following Classifications: ISO-L-HG 68.

CHARACTERISTICS (TYPICAL FIGURES)

EXIDIA EP 68

Viscosity at 100°C	mm ² /s	9.26
Viscosity at 40°C	mm ² /s	68.5
Viscosity Index	-	111
Flash Point	°C	236
Pour Point	°C	-15
Density at 29.5°C	gm/cc	0.87

* Also available in ISO VG 220

PROPERTIES AND PERFORMANC

- AGIP EXIDIA oils lubricate perfectly the guide-saddle connection of machine tools and prevent sticking and vibration, which influence the quality of finish of the machined item and the life of the tool.
- The additives contained in the product modify the static and dynamic friction coefficient values in order to avoid "stick-slip" phenomena and thereby ensuring a regular action of the machines and compliance with the requested tolerances.
- The formulation of the oils has been studied in order to ensure a good rust protection and a good demulsification of the oil, which is especially important for machines such as grinders in which water-based solutions are used as the cutting fluid.
- AGIP EXIDIA oils satisfy the Cincinnati Milacron thermal stability test. This test demonstrates the resistance to sludge and deposit formation and the absence of corrosion in iron and copper and their alloys, due to the temperature effect.
- The high viscosity index of this series of products guarantees a constant performance of the lubricant within a wide range of operating temperatures.
- AGIP EXIDIA oils posses high load resistance characteristics.

APPLICATIONS

AGIP EXIDIA oils have been studied and prepared especially for the lubrication of guides, even with high loads, with circulation and total loss lubrication systems.

AGIP EXIDIA 32 and 68 are also used as hydraulic fluids in those machines, especially grinding machines, in which a single oil is used for the lubrication of the guides and for the hydraulic drive.

AGIP EXDIA 220 may also be used for the lubrication of gears in those cases in which an oil with "antistick-slip" characteristics is expressly required, such as, for example, in the case of worm screws.

SPECIFICATIONS

AGIP EXIDIA oils satisfy the thermal stability and stick slip tests required by the specification:

- CINCINNATI P 53 (ISO VG 32), P 47 (ISO VG 68) and P 50 (ISO VG 220).

AGIP EXIDIA oils comply with the following specifications:

- ISO-L-HG 68
- STANIMUC G 32, 68 and 220
- DIN 51502 CGLP